



# CoverTec

innovative chemistry for substrate solutions

p: 754.223.2465 • f: 754.223.2467  
e: tec@covertecproducts.com

CoverTecProducts.com

Material Safety Data Sheet

## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** COVERCOAT 840 CP  
**PRODUCT DESCRIPTION:** ROOF COATING

**MANUFACTURER'S NAME:** COVERTEC PRODUCTS LLC  
10857 NW 50<sup>th</sup>. Street – Sunrise, Florida 33351

**INFORMATION TEL:** 754-223-2465  
**EMERGENCY TEL NUMBER:** INFOTRAC (800) 535-5053 OUTSIDE USA (352) 323-3500  
**DATE PREPARED:** JANUARY 2011

## SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
AROMATIC PETROLEUM DISTILLATES	64742-95-6	100PPM	100PPM	NONE	
*XYLENE	1330-20-7	100 PPM	100 PPM	150 PPM	7%
ZINC DIBUTYLDITHIOCARBAMATE	136-23-2	NONE	NONE	NONE	
ALICYCLIC HYDROCARBON RESIN	69430-35-9	NONE	NONE	NONE	
STYRENE/ETHYLENE/BUTYLENE BLOCK COPOLYMER	66070-58-4	NONE	NONE	NONE	
PIGMENT	NON HAZARDOUS IN LIQUID FORM	10mg/m3	10mg/m3	5mg/m3	
EXTENDER	NON HAZARDOUS IN LIQUID FORM	NONE	5mg/m3	NONE	

SECTION 2 NOTES: \*Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

## SECTION 3 – PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE AND ODOR:** WHITE OR COLORED MEDIUM VISCOSITY LIQUID  
**BOILING POINT OR RANGE:** 279F  
**VAPOR DENSITY (AIR = 1):** Not available  
**SPECIFIC GRAVITY (H<sub>2</sub>O = 1):** 1.2  
**EVAPORATION RATE:** not available  
**SOLUBILITY IN WATER:** NEGLIGIBLE

SECTION 3 NOTES:

## SECTION 4 – FIRE-FIGHTING MEASURES

**FLAMMABLE LIMITS IN AIR,**  
(% by volume) **UPPER:** not available  
**LOWER:** not available

**FLASH POINT:** 106F

**METHOD USED:**

SETA FLASH

**EXTINGUISHING MEDIA:**

FOAM, ALCOHOL FOAM, CO<sub>2</sub>, DRY CHEMICAL

**SPECIAL FIRE FIGHTING PROCEDURES:**

DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER. PRESENCE OF SOLVENTS IN PRODUCT MAY REQUIRE GROUNDING.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

IF FIRE OCCURS, SOLVENTS MAY PRODUCE EXCESSIVE PRESSURE. SEALED DRUMS MAY RUPTURE AND IGNITE. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND AND IGNITE BY ANY SOURCE OF IGNITION. NEVER USE A CUTTING OR WELDING TORCH NEAR CONTAINERS (EVEN EMPTY).

SECTION 4 NOTES:

## SECTION 5 – STABILITY AND REACTIVITY

**STABILITY:**  
STABLE



**CONDITIONS TO AVOID (STABILITY):**

AVOID EXCESSIVE HEAT OR OPEN FLAMES AS WELL AS ALL SOURCES OF IGNITION SUCH AS SPARKS, HEATERS, AND STATIC DISCHARGES ETC.

**INCOMPATIBILITY (MATERIAL TO AVOID):**

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:**

MAY FORM TOXIC CHEMICALS, CARBON DIOXIDE, CARBON MONOXIDE AND VARIOUS HYDROCARBONS ETC.

**HAZARDOUS POLYMERIZATION:**

WILL NOT OCCUR.

**SECTION 5 NOTES:**

**SECTION 6 – HAZARDS IDENTIFICATION**

**HMS HAZARD CLASSIFICATION**

HEALTH: 3      FLAMMIBILITY: 3      REACTIVITY: 0      PERSONAL PROTECTIVE EQUIPMENT: G

**POTENTIAL HEALTH EFFECTS**

**EYES:**

CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING OR BLURRED VISION.

**SKIN:**

MAY CAUSE IRRITATION, DEFATTING AND DERMATITIS.

**INGESTION:**

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA AND ASPIRATION OF MATERIAL INTO THE LUNGS

CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

**INHALATION:**

CAN CAUSE NAUSEA AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, AND POSSIBLE UNCONSCIOUSNESS.

**HEALTH HAZARDS (ACUTE AND CHRONIC):**

REPEATED CONTACT TO SKIN MAY CAUSE DEFFATING OR DRYNESS OF SKIN OR OTHER SIMILAR CONDITIONS. OVER-EXPOSURE TO THIS MATERIAL CAN CAUSE CARDIAC ABNORMALITITES, ANEMIA, LIVER ABNORMALITITES, KIDNEY DAMAGE OR EVEN EYE DAMAGE.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:**

RESPIRATORY CONDITIONS OF OTHER ALLERGIC RESPONSE.

**CARCINOGENICITY**

OSHA: NO      NTP: NO      IARC: NO

NPT PROGRAM- NO      IARC PROGRAM- NO

**ADDITIONAL CARCINOGENICITY INFORMATION:**

**SECTION 7 – FIRST AID MEASURES**

**EYES:**

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

**SKIN:**

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

**INGESTION:**

DO NOT INDUCE VOMITING, KEEP PERSON WARM AND CONSULT A PHYSICIAN IMMEDIATELY.

**INHALATION:**

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

**SECTION 7 NOTES:**

**SECTION 8 – RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. REMOVE ALL SOURCES OF IGNITIONS. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBANT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

**SECTION 8 NOTES:**



**CoverTec**  
innovative chemistry for substrate solutions

p: 754.223.2465 • f: 754.223.2467  
e: tec@covertecproducts.com

CoverTecProducts.com

Material Safety Data Sheet

#### SECTION 9 – WASTE DISPOSAL

**WASTE DISPOSAL METHOD:**

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

#### SECTION 10 – HANDLING AND STORAGE

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. PROPERLY LABEL ALL CONTAINERS. KEEP MATERIAL AWAY FROM ALL SOURCES OF IGNITION.

**OTHER PRECAUTIONS:**

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF. WEAR APPROPRIATE SAFETY EQUIPMENT AND RESPIRATOR AT ALL TIMES WHEN VENTILATION IS NOT SUFFICIENT TO CONTROL VAPORS.

**SECTION 10 NOTES:**

#### SECTION 11 – EXPOSURE CONTROLS/ PERSONAL PROTECTION

**RESPIRATORY PROTECTION:**

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. ENGINEERING OR ADMINISTRATIVE MEASURES SHOULD BE TAKEN TO REDUCE THE RISK AND EXPOSURE.

**VENTILATION:**

PROVIDE SUFFICIENT MECHANICAL (GENERAL AND LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TOXIC LEVEL VALUES.

**PROTECTIVE GLOVES:**

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

**EYE PROTECTION:**

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

**WORK HYGIENIC PRACTICES:**

OBSERVE GOOD GENERAL HYGENIC PRACTICES.

**SECTION 11 NOTES:**

#### SECTION 12 – TRANSPORTATION INFORMATION

DOT (SURFACE & AIR):	FLAMMABLE LIQUID N.O.S. 3 UN1993, PGIII
IMO (OCEAN):	FLAMMABLE LIQUID N.O.S. 3 UN1993, PGIII
IATA (AIR):	FLAMMABLE LIQUID N.O.S. 3 UN1993, PGIII

**REQUIREMENTS : FLAMMABLE LABEL**

---

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, expressed or implied, and we assume no responsibility for any loss, damage, expense, direct or consequential, arising from their use.

---