Ceramic, Porcelain & Stone Tile

Street and and a

GlazeGuard PLUS

Anti-Slip Formula Developed Specifically for Sealing Ceramic and Porcelain Tile and Grout

Ultra Durable Clear Highly Slip Resistance Sealer for Ceramic, Porcelain & Stone Tile Surfaces

GlazeGuard® with CoverGrip creates GlazeGuard® Plus, a solvent-free, virtually odorless, urethane coating with exceptional adhesion and performance properties. The addition of CoverGrip achieves high slip resistance significantly reducing the potential for a slip in accordance with the National Floor Safety Institute (NFSI) standards. It is suitable for virtually any vertical or horizontal surface with inherent chemical resistance, stain and wear resistance properties.



GlazeGuard® Plus, dramatically increase the slip resistance of indoor and outdoor floors to make them safer for pedestrians!

EXCEPTIONAL PERFORMANCE

The bonding capabilities including porcelain and ceramic tiles, ferrous and non-ferrous metals, and many other surfaces that other coatings will not adhere to. Ideal for car parks, high traffic corridors, transport terminals, warehouses, fabricated metal products, and most very high traffic applications - both internal and external.

GlazeGuard Plus anti-slip floor treatment designed to give the coefficient of friction (grip/traction) levels that are safer in wet or dry conditions. GlazeGuard Plus is classified as a **High Traction, High Slip Resistance** floor finish, exceeding traditional wax and acrylic finishes (wet or dry) and meeting and exceeding ADA standards. The product has been independently tested in accordance with the Nation Floor Safety Institute (NFSI) and has a Wet DCOF of > 0.6 or more* for wet walkway surfaces. Simply put, you can lower slip/fall injury risk and control walkway slip resistance using this flooring system.



Typical Uses



- Tiles ceramic, terrazzo, porcelain, stone porous to a high gloss
- Resilient Floors vinyl, rubber, linoleum
- Timber sports floors, engineered and solid timber floors, parquetry, decks, doors, tables
- Concrete floors, parking decks, warehouses, walkways, stairs, walls, benchtops
- Metal ferrous and nonferrous metals, fabricated metal products, doors, boat trailers

Stain Resistant • Restores Luster and Color • Forms Protective Shield • Easy Cleaning

COMPLETE ALL IN ONE EASY TO MIX AND APPLY ONE COAT SYSTEM



GlazeGuard with CoverGrip Requires Minimal Downtime with a One Coat Application

About CoverGrip™

CoverGrip Additives turn almost any floor finish (concrete, vinyl, rubber, timber, tile, stone, etc.) into a slip-resistant surface. With the addition of grip additives to the clear (gloss, satin or matte) sealer, the product can provide a Wet Dynamic Coefficient of friction (WDCOF) of 0.6 or greater*. They provide an ideal finish for kitchens and food prep areas, pedestrian ramps and any areas requiring an anti-slip surface.



NON SLIP ENHANCEMENT

Our easy to apply formulas not only enhance the appearance and protection they also increase slip-resistant properties for an even safer surface.



FAST APPLICATION TIME

One coat system means many applications can be completed in a single night avoiding loss of trade and minimizing disruption. One coat application also significantly reduces labor costs.**



ENVIRONMENT SAFE

Proprietary formulation uses water as a solvent and eliminates traditional solvents and all the hazards and odor associated with them.



Applications

- Rejuvenate ceramic, porcelain, terrazzo, stone
- · Provide hygienic protection for grout lines on floors and walls
- · Restore existing vinyl, rubber or linoleum to remove scratching
- Improve the appearance and reduce cleaning costs
- Seal or color concrete floors in corridors, kitchens, warehouses
- Superior finish where gloss enamel paints are required
- Timber sports floors, hardwood floors, covered decking
- Other engineered or solid timber floors including parquetry
- Metal surfaces including steel door frames, stairs
- Cover plates, trailers, and engineered metal products
- Seal or color concrete car parks, including safety line marking, logos and lettering

LOW TO ZERO VOCS AND VIRTUALLY ODORLESS

GlazeGuard Plus[™] is produced using water as a solvent and does not use traditional solvents or co-solvents. It has no free monomers when parts A and B are mixed. The result is a virtually odorless, very low to zero VOC product that can be applied in sensitive areas, such as patient care and sterile areas, without affecting the surrounding areas.

* Slip ratings are surface dependent. Always test before application.

** Dry times are affected by environmental conditions such as temperature and humidity. Always test before application.

Reduces Falls • Highly Slip Resistant • Independently Tested • Meets NFSI Standards

Easy to Apply:

BY MICROFIBER ROLLER WITH 3/8" NAP OR SPRAYER, SPREAD 1 THIN EVEN LAYER

THEORETICALCOVERAGE

Approximately 500ft²/gallon (12.2 m2 /liter) depending on the size density and porosity of the grout joints



Wood Look Tile

Non Yellowing UV Resistance



Stain Resistance & Easy to Clean

GlazeGuard Plus

with CoverGrip

Complete One Coat Application System

Application: Microfiber roller, Low-pressure spray Available Finishes: Gloss, Satin and Matte



Dry Time: Light Foot Traffic 12 hrs Heavy Foot Traffic 24 hrs (1 thin coat recommended) Microfiber roller w 3/8" nap or sprayer



Exposure Conditions: Moderate chemical & wear resistance Base: Water Base, Zero odor Provides a Wet Dynamic Coefficient of friction (WDCOF) of 0.6 or greater* Maintain & Clean: Mild liquid detergents, neutral cleaner or enzyme cleaner



Restuarant





Entrance Way

Seals, Protects, Beautifies & Reduces Falls